

# SUMMIT

DOUBLE  
3THREE

TRIPLE  
5ZERO

QUAD  
6FIVE



The WEST Summit Series utilizes our advanced Optimized Supercapacitor storage technology. Benefits include negligible degradation over lifetime, ultra-fast charge and discharge, no thermal runaway hazard, simple operation, practically unlimited cycles, -40°C to 65°C operating temperature, and 97% round-trip efficiency.

The Summit Series is specifically designed to be used in a wide range of inverter or DC-based applications, including solar, backup, mobility, grid storage, recreational, and much more. Energy can be safely used with our EZPower® technology. The EZPower® features include short circuit detection, multiple unit imbalance control, and controlled load charge-up.

Utilize our remote monitoring for Android and iOS through Wi-Fi and set up with our user-friendly app for mobile devices. Units are completely modular with unlimited parallel compatibility. Designed for extremely long life (up to 45 years).

The WEST Summit Series is the ultimate choice in contemporary storage technologies

**45 year**  
Design Life

**20 year**  
Warranty

**Remote**  
Monitoring



## OPTIMIZED SUPERCAPACITOR ENERGY STORAGE

Ultra long cycle and operational life (45 years design life)

Fast charge and discharge

Temperature stability – no thermal runaway

Wider operating temperature range compared to other storage technologies

99.1% capacitor RTE, >97% module RTE

Safer energy storage

## COMPLETE SYSTEM MONITORING

Dual current management for added safety

Patented CLC for controlled power release and safety checks

## 20 YEAR WARRANTY<sup>1</sup>

### GENERAL

Storage Type	Optimized Supercapacitor
Monitoring	Wi-Fi, Android, IOS
Communication	Wi-Fi, LED Status
Operating Temperature	-40°C to 65°C
Cycle Life/Warranty	5x Lithium / 20 year warranty <sup>1</sup>
Design Life	45 Years
Terminal Connections	M8
Round Trip Efficiency	>97%
IP Rating	IP30

### SPECIFICATIONS

	DOUBLE 3THREE	TRIPLE 5ZERO	QUAD 6FIVE
Capacity (kWh / Ah)	3.3 / 67	4.95 / 100	6.6 / 134
Module Weight (kg)	72.6 kg	97 kg	128.6 kg
Crate Weight (kg)	10 kg	11.5 kg	14.2 kg
Dimensions (mm) L x W x H	580 x 632 x 170	580 x 632 x 245	580 x 632 x 320
Dimensions (In) L x W x H	22.83 x 24.88 x 6.69	22.83 x 24.88 x 9.65	22.83 x 24.88 x 12.6
Stackable (units)	6 Units	5 Units	3 Units

### CHARGE / DISCHARGE

Rated Charge Voltage (V)	53.6 V	53.6 V	53.6 V
Maximum Continuous Charge Voltage	53.6 V	53.6 V	53.6 V
Maximum Surge Voltage (V)	54.0 V	54.0 V	54.0 V
Recommended Discharge Voltage (V)	46.0 V	46.0 V	46.0 V
Rated Discharge Voltage (V)	45.5 V	45.5 V	45.5 V
Maximum Continuous Current (A)	100 A	200 A	250 A
Maximum Peak Current (A)	125 A	250 A	250 A
Maximum Charge/Discharge Rate (C)	1.5 C	2 C	1.5 C

### SAFETY

Current Safety	Electronic SSR and Thermal DC Breaker (Dual Protection)
Maximum Capacitor Voltage	Electronic
Loose Connection Monitoring	Electronic
Temperature Monitoring	Electronic
Cell Temperature Monitoring	Electronic
Safe Activation Parameters	WEST EZPower® limited energy release

1) Please refer to the Warranty Document for applicable conditions.  
For more information, please contact us at [info@wright.energy](mailto:info@wright.energy)